SMART MAG TOOL FOR GLOCK


FAST, EASY GLOCK MAGAZINE DISASSEMBLY AND NO FLYING SPRINGS.

Change base plates or disassemble Glock OEM magazines for safe and easy cleaning. No fumbling, no need for an extra hand, no out of control springs launching across the room. The Smart Mag Tool for Glock simplifies the process by allowing you to break open the baseplate, and slide it off while retaining the spring in a secure position. To assemble, just reverse the operation. A once clumsy task has been rendered easy. It's called the Smart Mag Tool. Maybe it should be called the Easy Mag Tool.


MAGAZINE QUICK-DISASSEMBLY TOOL








Step 1: Place rubber overmolded base on table, insert post 1 into magazine release port on bottom of base plate, then lever downward to crack loose base plate.



Step 2: Place magazine on top of tool and insert post 2 into base plate port. **Step 3:** While pressing down, slide the magazine backrward to remove the base plate and capture the spring.



Step 4: To reassemble, place base plate onto post 2. Step 5: Place spring retention plate onto the tool with the tab resting downward into the small groove. Step 6: Insert the spring into the magazine, being careful to orient the spring in the correct direction.



Step 7: While holding the magazine, place the spring onto the spring retention plate and press down firmly until the rim of magazine housing is resting on the top of the tool surface. Step 8: Slide the magazine forward into the base plate locking it into place.

WARNING: This product can expose you to chemicals including 4,4'-Methylenedianiline, which is known to the state of California to cause cancer and birth defects or reproductive harm. For more information, go to www.P65Warnings.ca.gov.



