

# GUN BOSS® PRO - AR15

The Gun Boss® Pro AR15 system cleans and protects AR15's with task specific high-quality tools in a compact, organized tool case. Follow these simple steps when cleaning your rifle to ensure proper function and reliability.

## SAFETY FIRST

**BE SURE YOUR FIREARM IS UNLOADED: PUT THE FIREARM ON "SAFE." REMOVE THE MAGAZINE. PULL BACK ON THE CHARGING HANDLE, AND MAKE CERTAIN THAT THE CHAMBER IS EMPTY. WORK IN A WELL VENTILATED AREA AND WEAR EYE AND HAND PROTECTION.**


**NOTE:** The preferred direction for all bore cleaning is from action to muzzle. During cleaning it is also important that the barrel is angled so that excess solvent will exit the muzzle and not drain back into the action.

## CLEANING INSTRUCTIONS FOR 5.56/.223 AR15's

**STEP 1:** Connect one cleaning rod to the non-rotating threads on the rod handle. Then connect the chamber brush to the other end of the rod. Apply a light amount of solvent to the bristles.



**STEP 2:** Insert the chamber brush into the chamber and rotate clockwise to loosen fouling.



**STEP 3:** Replace the chamber brush with the male thread adaptor and a wool star chamber pad. Apply a few drops of solvent to star chamber pad. Insert star chamber pad and rotate clockwise to absorb the loosened fouling. Repeat this step using additional star chamber pads until they come out clean.


For stubborn fouling remaining in the chamber use the included pick set to gently dislodge it. Do not apply an excessive amount of force to the picks. Excessive force may cause damage to the picks and/or the firearm. When finished, remove rod from T-handle.



**STEP 4:** Locate the rotating threaded section on the rod handle. Using the rotating threads, connect the appropriate number of rods to clean the full length of the rifle's bore.




**STEP 5:** Attach the slotted tip to the end of the rod. Slide a cleaning patch through tip. Apply a generous amount of solvent to the patch.




# CLEANING INSTRUCTIONS CONTINUED...

**STEP 6:** While guiding the rod with both hands, push the patch through bore from action to muzzle. Wait several minutes for solvent to work properly (as instructed by the manufacturer).



**STEP 7:** Attach the bore brush to the rod. Guide the rod and push the brush through bore from action to muzzle. This step will loosen the fouling.



**STEP 8:** Re-attach the slotted tip to the rod, then push a clean patch through the bore. This patch will absorb loosened fouling. Repeat steps 5 through 8 until the last patch comes out clean.



**STEP 9:** Proceed to wipe down the action with a clean patch lightly coated in solvent. Stubborn fouling may be removed with the nylon brush. Finally, wipe down action with a clean dry patch to remove remaining fouling as well as any excess solvent.



**STEP 10:** Maintaining a clean bolt carrier group is also essential to proper AR15 function. Remove any excess carbon build up using solvent along with the brushes and picks included in this kit.

We also recommend the use of a high quality scraper such as “The AR15 Scraper” by Real Avid. The “AR15 Field Guide” by Real Avid is another great addition to your cleaning kit. The AR15 Field Guide uses colored illustrations to depict the parts, disassembly, cleaning, and lubrication necessary for proper AR15 function.

**NOTE:** After handling a firearm it is good practice to wipe down external metal components with a very light coat of CLP or gun oil to reduce oxidation.

## TOOL CASE:

**THE TOOL CASE FOR THE GUN BOSS PRO IS AN ORGANIZED, STURDY AND SECURE STORAGE SOLUTION FOR GUN MAINTENANCE. IT IS MADE FROM IMPACT-RESISTANT POLYCARBONATE. IT CAN ALSO BE USED AND STORED IN A VARIETY OF POSITIONS AS LISTED BELOW:**

**STOW AND GO:** In this compact position the case stores virtually anywhere. Simply lock it shut and it is ready for your range bag, tool box, truck or ATV.

**PEG BOARD:** The convenient hole in the top of the case allows for easy storage on any peg board or hook in your workshop.

**WORK BENCH:** When opening the case, the clear cover rotates around to form a kickstand for the rest of the case. This allows for organized cleaning on any flat surface.

**WALL MOUNT:** Locate the two small holes behind the rod handle. These holes are sized to accept a standard drywall screw. This allows you to permanently mount the case to any wall of your choice.



Revo Brand Group, LLC • 5480 Nathan Lane North, Suite 120  
Minneapolis, MN 55442 USA

RealAvid.com • 800-286-0567

©2018 Revo Brand Group